



UT447E(V)

0.5GPF Low Consumption Washout Urinal

FEATURES

- Compact urinal with concealed integral trap
- Washout flush action with 3/4" top or back spud inlet
- 0.5 GPF with any flush valve shown below

MODELS

- UT447E
Urinal with 3/4" top spud inlet
- UT447EV
Urinal with 3/4" back spud inlet

ADDITIONAL ITEMS (sold separately)

- THU3017
Stainless Steel Urinal Drain Cover


RECOMMENDED FLUSH VALVES		
UT447E		UT447EV
EcoPower®	Manual	EcoPower®
TEU1LN12#CP	TMU1LN12#CP	TEU2LN11#SS
		TEU3LN11#SS

COLORS/FINISHES

- Standard
#01 Cotton
#03 Bone
#12 Sedona Beige

PRODUCT SPECIFICATION

The wall-mounted, ADA compliant, low consumption washout urinal shall be 0.5GPF/1.9LPF when paired with a 0.5GPF flushometer valve and 1.0GPF/3.8LPF when paired with 1.0GPF/3.8LPF flushometer valve. Urinal specified shall be model UT447E_____.



CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1,
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative compliance: California AB715, California Green Building Code
- ADA compliant




UT447E(V)

0.5GPF Low Consumption Washout Urinal

SPECIFICATIONS

• Water Use	0.5GPF/1.9LPF
• Flush System	Washout flush action
• Warranty	One Year Limited Warranty
• Material	Vitreous china
• Min. Water Pressure	15 psi (flowing)
• Height (Urinal Only)	27-3/16"
• Width	18"
• Rim	14"
• Shipping Weight	UT447E(V) - 60lbs
• Shipping Dimensions	UT447E(V) 29-7/8" L x 16-3/4" W x 19-1/8" H

UT447E



UT447EV

