



Geberit Duofix element for wall-hung WC, 114 cm, with Alpha concealed cistern 8 cm



Example image



Application purposes

- For drywall construction
- For installation in part- or room-height prewall installations
- For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For dual flush
- For floor constructions 0–20 cm

Characteristics

- Self-supporting frame, powder-coated
- Frame top open
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- Galvanized feet
- Feet adjustable 0–20 cm
- Connection bend can be mounted without tools
- Minimum depth to the middle of connection bend 9 cm
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation

- Immediate post flush possible with factory setting
- Water supply connection on the top left

Technical data

Flow pressure	0.1-10 bar
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5 l
Flush volume small, adjustment range	3-4 l

Scope of delivery

- Water supply connection Rp 1/2" - R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- Protection box for service opening, made of polystyrene foam
- 2 wall anchors
- Connection set for WC, ø 90 mm
- Connection bend made of PE-HD, ø 90 mm
- Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

Art. no.	B	H	T
458.176.00.1	50 cm	114 cm	13.5–20 cm

Accessories

- Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- Geberit DuofixBasic set of wall anchors for single installation



- Actuator plate has to be ordered separately